



Meeting the Challenges of Calibrating HD ICEs for Real-World and In-Service Emissions Compliance using AI-driven Empirical Digital Twins

Steve Whelan, HORIBA Global Applications Leader, HORIBA MIRA Ltd, UK

FPC2026
Future Propulsion Conference

Contents


- Introduction – What is a Digital Twin and what are the benefits?
- HORIBA Empirical ICE Digital Twinning Toolset
- Non-Road Mobile Machine Training Cycle and Model Validation
- Non-Road Mobile Machine Simulations
- Non-Road Mobile Machine Performance and Emissions Predictions
- Conclusions

Contents

- Introduction – What is a Digital Twin and what are the benefits?
- HORIBA Empirical ICE Digital Twinning Toolset
- Non-Road Mobile Machine Training Cycle and Model Validation
- Non-Road Mobile Machine Simulations
- Non-Road Mobile Machine Performance and Emissions Predictions
- Conclusions

Empirical or Data-Driven Digital Twin: What is it?

- A pseudo-perfect digital representation of a physical object.
- Empirically based and created with 'real' data.
- Empirical models of different attributes i.e., fuel economy, NOx, battery attributes, power consumption reside within the EDT.
- These models are subsequently used to predict responses for specific inputs.




The New HD Challenge of Real World Emissions Compliance

ISC and RDE will impact NRMM & HDV ICEs, whatever type of decarbonised fuel is used

NRMM Stage VI ISC


- In-Service Monitoring introduced in 2016
 - Commission Delegated Regulation (EU) 2017/655 of 19 December 2016 (56 to 560kW engines)
 - CO, CO₂, NO_x, THC
 - Reporting due now



Stage VI:
Mandatory ISC in 2032

Heavy Duty Euro 7 – RDE & ISC

- Trip composition governed by Euro6e RDE-like criteria
 - Any driver aggressivity
 - RDE Conformity Factors of 1.0
 - Whole life factor of 1.2
 - 875,000k/10 years ISC
- New measurements: + PN10, NMHC, NH₃,
 - From cold (2km @ <20% power)
 - Brake & Tyre PM/PN
 - Battery durability
 - On-Board Monitoring



- Any trip with >6% rated power condition.
- Any application within legal limits
- Makes engineering and V&V process much harder.
- “Infinite” scenarios

Coping with “Infinite” Scenarios Without “Infinite” costs!

Achieve sufficient coverage using predictive simulation

- Almost “infinite” drive-case scenarios in Euro 7 and In-Service Compliance NRMM Stage VI
- Impossible to physically test and validate all drive cases

Solution


- Use simulation to identify worse cases
- Physically test worst cases only (far fewer tests)
- Use simulation to populate the validation



- **Physical** ‘Worst case’ Road test
Lab Replication & Emulation




- **Simulation** Empirical Digital Twin +
Co-simulation



Reducing the Need for Physical Testing – Reduce Time & Cost

- Include accurate simulation as part of the validation and sign-off process to avoid extra testing




Contents

- Introduction – What is a Digital Twin and what are the benefits?
- **HORIBA Empirical ICE Digital Twinning Process**
- Non-Road Mobile Machine Training Cycle and Model Validation
- Non-Road Mobile Machine Simulations
- Non-Road Mobile Machine Performance and Emissions Predictions
- Conclusions


HORIBA Empirical (Data-Driven) ICE Digital Twin

Test Designer




Transient excitation signal design specific to the unit under test

AI Modeller



Rapid generation of transient empirical models using AI recurrent neural networks

Predictor



Prediction of attributes using transient empirical models at faster than real-time

Optimiser




Multi-objective optimiser and 'hot-spot' identification toolset for improved performance

Neural Networks

General Purpose Predictor


- Neural networks are a complex structure of simple operations
- They are generated by varying those simple operations and comparing the resultant output to a measured value. The aim is to minimise the difference across the whole dataset
- Completely Black Box and uninterpretable, but well established and have been shown to exhibit very good performance across a wide range of applications
- (Usually) takes a lot of data and time to train
- Predict extremely quickly
- Readily accelerated with GPU computation



Neural Networks


General Purpose Predictor

- Neural networks are a complex structure of simple operations
- They are generated by varying those simple operations and comparing the resultant output to a measured value. The aim is to minimise the difference across the whole dataset
- Completely Black Box and uninterpretable, but well established and have been shown to exhibit very good performance across a wide range of applications
- (Usually) takes a lot of data and time to train
- Predict extremely quickly
- Readily accelerated with GPU computation



Modelling Method Evaluation


Model	Training Time (dynamic DOE dataset)	Prediction Time (test dataset)
SPM	Several minutes	~60 seconds
Neural Network	~1.5-5 minutes	~0.1-0.5 seconds
LOLIMOT	~2.5-25 minutes	~0.01-0.5 seconds
HILOMOT	~10-100 minutes	~0.02-0.1 seconds
Genetic Programming	~5-45 minutes	~0.01-0.1 seconds



Intelligent Lab Recurrent Neural Network (RNN) Approach

Adding Memory, Dynamic Capability

- Adding LSTM (Long Short Term Memory) nodes to the network allows the model to look at not just the instantaneous data, but sequences of data and the history of the system.
- Systems with time dependent phenomena (dynamics) can be accurately reproduced.
- Dynamic capability allows prediction of e.g. NO_x
- Scales to meet the complexity of your problem
- Intelligent test design allows fast training times with minimal data due to high data quality and information density.
- **RNN delivers optimum solution for training & prediction**



Digital Twinning Creation & Validation


1. Experiment design

Create the transient training cycle using HORIBA Intelligent Lab toolset




2. Training data

Record training data from the unit under test (engine, powertrain, motor, battery)




3. Model creation

Create transient empirical models of various performance and emissions attributes



4. Model validation

Validate transient empirical models to ensure high quality and fidelity



Digital Twin Usage – ICE Application Calibration


5. Virtual or Real Scenarios

Create real-world machine cycles using software or use physical real-world data and couple with EDT




6. Predict Responses

Predict attributes for the scenarios created using the empirical models



7. 'Hotspot' Recalibration

Identify 'hotspots' and recalibrate/change hardware to improve cycle results




Contents

- Introduction – What is a Digital Twin and what are the benefits?
- HORIBA Empirical ICE Digital Twinning Toolset
- **Non-Road Mobile Machine Training Cycle and Model Validation**
- Non-Road Mobile Machine Simulations
- Non-Road Mobile Machine Performance and Emissions Predictions
- Conclusions


NRMM ICE EDT Training Cycle – Dynamic DoE Design

Operating Space Coverage



The transient training cycle should cover the entire operating space of the unit under test; mitigates the need for extrapolation during modelling



Real-world Representative Transients



Real-world transient operation of the unit under test should be considered during design of the training cycle; variable transient operation is possible

EDT Model Validation Technique



Validation cycle
Run the cycle on the engine



Measured data


Predicted data

Validation cycle
Run the cycle through the EDT





EDT Model Validation Technique

Validation cycle
Run the cycle on the engine




Validation cycle
Run the cycle through the EDT




measured data

redicted data




Empirical Model Quality – Fuel Mass Flow

*NRTC Validation Cycle




Real World Validation Cycle




* Non-Road Transient Cycle

Empirical Model Quality – Engine Out CO₂

*NRTC Validation Cycle




Real World Validation Cycle




* Non-Road Transient Cycle

Empirical Model Quality – Engine Out NOx

*NRTC Validation Cycle



Real World Validation Cycle




* Non-Road Transient Cycle

Contents

- Introduction – What is a Digital Twin and what are the benefits?
- HORIBA Empirical ICE Digital Twinning Toolset
- Non-Road Mobile Machine Training Cycle and Model Validation
- **Non-Road Mobile Machine Simulations**
- Non-Road Mobile Machine Performance and Emissions Predictions
- Conclusions

Co-simulation of Virtual Scenarios with Empirical Models (1)

- 1.) Machine operation – field, accessories, hydraulic loadings, or roading including trailer towing using AgriSI software from Soluzioni Ingegneria virtual agricultural simulation software.
- 2.) Extract data for use with models e.g. engine speed and torque.
- 3.) Couple with empirical models from the EDT.
- 4.) Predict performance and emissions attributes.



Co-simulation of Virtual Scenarios with Empirical Models (2)

- 5 different types of simulations were created: fertilising, spraying, ploughing, seeding, and roading.
- The terrain and soil depth were varied along with trailer weight during roading.
- Engine out performance and emissions were subsequently predicted for a total of 10 simulations.



Co-simulation of Virtual Scenarios with Empirical Models (2)




Contents

- Introduction – What is a Digital Twin and what are the benefits?
- HORIBA Empirical ICE Digital Twinning Toolset
- Non-Road Mobile Machine Training Cycle and Model Validation
- Non-Road Mobile Machine Simulations
- **Non-Road Mobile Machine Performance and Emissions Predictions**
- Conclusions



Prediction of Performance and Emissions

Ploughing, 150mm & 200mm Soil Depth




Prediction of Performance and Emissions

Spraying, Hilly Field & Flat Field





Prediction of Performance and Emissions

Roading with Trailer, Empty, Half Full, Full



Rapid Focus on Critical Attributes

- Data from all simulations was combined. NOx and time data was ‘binned’ for given speed/load ranges.
- Residency plots allow identification of **Hotspots** – small time residency, high emissions.
- **Improve the calibration or hardware at Hotspot location – improved efficiency, reduced emissions.**
- Time residency – identification of most common operating conditions across cycles or machines = **robust calibration.**




Contents

- Introduction – What is a Digital Twin and what are the benefits?
- HORIBA Empirical ICE Digital Twinning Toolset
- Non-Road Mobile Machine Training Cycle and Model Validation
- Non-Road Mobile Machine Simulations
- Non-Road Mobile Machine Performance and Emissions Predictions
- **Conclusions**

Multiple Machines, Fuels & Applications


- Powertrain sharing is common for off-highway manufacturers
- Powertrain digital twins with new fuels can be applied to machines and scenarios




- Accelerated software development
- Increased certainty with decarbonised fuels
- Reduced product cost, risk & warranty



Test Scenarios
Vehicle, Fuels, Terrain and Environment



Dynamic Empirical Models
Performance and emissions



Predictions
Fuel, air, NOx, PN, NH3, N2O, electric range, CO2eq

Omoshiro-okashiku
Joy and Fun



Thank you

Cảm ơn

감사합니다

ありがとうございました

Dziękuję

धन्यवाद

Grazie

Merci

谢谢

ขอบคุณครับ

நன்றி

Gracias

Obrigado

Σας ευχαριστούμε

Děkuji

Teşekkürler

شكرا

Tack ska ni ha

Danke

Большое спасибо